

20 May 2013
Europeimports Pty
3/6 Gladstone St
Castle Hill 2154

Attention Carl Yench

Re Examination of Ezarri 25mm x 25mm spot jointed glass mosaic tiles and technical opinion of CTA recommended adhesives and grouts

This specification must be read in conjunction with Australian Standards AS 3958.1-1991, Guide to the installation of ceramic tiles” and the printed directions on all the product packaging.

When used in accordance with the above Australian Standards and the printed directions on the packaging, CTA Pty Ltd guarantees the performance of its products for a period of 12 (twelve) years. This specification should be read in conjunction with the product technical sheets. (See attached)

All surfaces must be firm, rigid, clean, dry, sound and smooth. All grease, wax, oil, curing compounds, release agents, dust, plaster droppings and paint must be removed from the surface prior to the application of the any products.

1. Description of sample supplied

Blue Ezarri 25 x 25mm spot jointed glass mosaic with 2mm gap between each tile.
No mesh on tile

2. Recommendation

CTA recommends that the following adhesives and grouts would be suitable for the installation of the specified glass mosaic tiles to a concrete rendered swimming pool in a fully immersed application.

Adhesives

- a. CTA Pro Premium
- b. CTA Ultrapro
- c. CTA Proset Super/CTA Prolastic neat

Grout

- a. CTA Polyblend G10 Grout (select colour)

CTA guarantee the specified systems for 12 years provided application is in accordance with manufacturer’s written directions for use and the Australian Standard AS 4992.1. The representations and recommendations regarding the products are based on tests which we believe to be reliable.

Charlie Graham

CTA Sales Manager